

NAS1045Thimble-Heavy
(Wire Cable)

Steel

NAS1098Nut, Tube
FittingAluminum
Steel
CRES. Steel**NAS1193**

Locking Device

CRES. Steel (4104)
17-4 PH**NAS1046-1053**Clip-Wire Rope;
Turn Buckle;
Chain-Welded;
Slinglink, Hooks;
Eye BoltSteel
Alloy Steel**NAS1100-1102**Screw,
Torq-Set®
Full ThreadAlloy Steel
CRES. Steel
(A-286)
3A Fit**NAS1195**Shim, Anchor
Nut; MiniatureSteel
CRES. Steel
Al Clad
Al Alloy
Titanium
Al Alloy**NAS1061**Lockwasher
High-Temperature

CRES. Steel

Flat
Fillister Pan Head100° Flat Head
Coarse and Fine Thread**NAS1197**

Washer, Flat




CRES. (A-286)

NAS1067-1068Nut, Plate
Self-locking
500°F, 800°FSteel
CRES. Steel
3B Fit**NAS1103-1120**Bolt, Hex Head
Close Tolerance
160,000 psi
Drilled Shank/UndrilledAlloy Steel
3A Fit**NAS1198-1200**


Rivet, Solid

**NAS1071-1073**Switch Toggle;
and Guards


Steel

Nut
MS25062Screw
AN508Locking
Ring
MS25081Lockwasher
AN935**NAS1121-1128
NAS1131-1138**Bolt, Torq-Set®
Short ThreadAlloy Steel
CRES. (A-286)
*Ti Alloy
3A Fit


Flat Fillister Pan Head

NAS1201Bead Chain
Components and
AssemblyBrass
CRES. SteelALSO SEE MS25016/MS35058/
MS35059/MS25068**NAS1080**Collar
LockboltAluminum
Steel**NAS1141-1148
NAS1151-1158**Bolt, Torq-Set®
Short ThreadAlloy Steel
CRES. (A-286)
*Ti Alloy
3A Fit


Brazier Head 100° Flat Head

NAS1211-1213Fitting, Tie Down
Strap End; StrapSteel
Al Alloy
Cotton
NylonSet Screw,
Self-Locking
Hex Socket;
250°FAlloy Steel
CRES. Steel
3A FitType A
Flat Pt.Type B
Cone Pt.Type D
Cup Pt.


*Per NAS621 (4Al-4Mn and 6Al-4V)

NAS1216-1218Pan Head
"Hi-Torque®"
BoltCRES. Steel
Alloy Steel
CRES. (A-286)
3A FitFull
ThreadShort
Thread


Long Thread

NAS1083-1088Bolt 100°
Flat Head,
Close
ToleranceTi Alloy
Per NAS621®"Hi-Torque®"
Recess "Phillips"
Recess


*4Al-4Mn and 6Al-4V

NAS1161-1168Bolt, Self-Locking
Torq-SetAlloy Steel
Available in
CRES. (A-286)
3A Fit


100° Flat Head

NAS1219-1221100° CTSK.
"Hi-Torque®"
BoltCRES. Steel
Alloy Steel
CRES. (A-286)
3A FitFull
ThreadShort
ThreadLong
Thread**NAS1096**Screw-Hex
Head, Recessed

Alloy Steel

**NAS1171-1178
NAS1181-1188**Bolt, Self-Locking
Torq-Set® 250°Alloy Steel
Available in
CRES. (A-286)
3A Fit**NAS1097**Rivet-Solid
100° Flush
Shear

Al Alloy

NAS1189-1191Screw, Self-Locking
Full Thread, 250°
Phillips and
Torq-Set®Alloy Steel
CRES. (A-286)
3A Fit